

## Approvals



10A-300V

## Electrical

|                       |                             |
|-----------------------|-----------------------------|
| Rated voltage         | 130V                        |
| Rated current         | 10A                         |
| Contact resistance    | 20mΩ                        |
| Insulation resistance | 500MΩ/DC500V                |
| Withstanding voltage  | AC200V/1 min                |
| Wire range            | 28-14AWG 1,5mm <sup>2</sup> |

|                  |             |
|------------------|-------------|
| Torque           |             |
| Temp. Range      | -40°C+105°C |
| Stripping length | 8 mm        |
| Max sold. time   |             |

## Dimensions

|       |        |
|-------|--------|
| Pitch | 3,81mm |
| Poles | 2+24   |

## Material

|            |                          |
|------------|--------------------------|
| Housing    | PA66 UL94V0              |
| Pin        | Copper Alloy, tin plated |
| Cage       |                          |
| Screws     |                          |
| Side Block |                          |
| Nut screw  |                          |
| Clamp      | Stainless Steel          |

## General description of ordering code

| Series | n. Poles | Pitch | Version | Color | Custom |
|--------|----------|-------|---------|-------|--------|
| CFP1   | 02+24    | -3.81 |         |       |        |

## Version Date

01/17 20/04/17

