



Approvals



15A-300V
not approved

Electrical

Rated voltage 320V
Rated current 20A
Contact resistance 20mΩ
Insulation resistance 500MΩ/DC500V
Withstanding voltage AC2000V/1 min
Wire range 28-14 AWG 2,5 mm²

Torque 0,5Nm(4.5 Lb in)
Temp. Range -40°C + 105°C
Stripping length 7 mm
Max sold. time

Dimensions

Pitch 7,5 mm
Poles 2±24

Material

Housing PA66 UL94V0
Pin Copper Alloy, Ni plated
Cage M3 Steel, Zn plated
Screws M3 Steel, Zn plated
Side Block Phosphore Bronze, Ni plated
Nut screw
Clamp

General description of ordering code

| Series | n. Poles | Pitch | Version | Color | Custom |
|--------|----------|-------|---------|-------|--------|
| CRV | 02±24 | -7.5 | -L | | |

Version Date

17/01 26/10/17



| UNITS: mm | | SHEET SIZE: ISO A4 | | SCALE: 10:1 | |
|-----------|----------|--------------------|------------|-------------|--|
| > 0 ~ 3 | > 3 ~ 18 | > 18 ~ 50 | > 50 ~ 120 | | |
| ± 0.12 | ± 0.15 | ± 0.3 | ± 0.5 | | |



CRV-7.5-L