

# FEMALE HEADER SMT SINGLE ROW U-TYPE SIDE ENTRY


## 23 SERIES - 2.00MM PITCH



### Specifications

- Rated Current: 1.5AMP
- Contact Resistance: 20mΩ Max
- Withstand Resistance: 500V AC/DC
- Insulation Resistance: 1000MΩ Min
- Operation Temperature: -40°C to +105°C
- Contact Material: Brass
- Contact Plating : Au Or Sn Over Ni
- Insulator Material : Polyester (UL94V-0)
- Standard : PA6T
- Max. Processing Temp : 230° for 30-60 seconds  
260° for 10 seconds

Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE±0.05)



### Ordering Information

**2345S - 1 U (XX) - A B C (1)**  
1 2 3 4 5 6 7

#### 1. Connector Series

#### 2. (H) Hauteur isolant

- H = 45 (Hauteur isolant : 4.5mm)

#### 3. U-Type

#### 4. Number of pins per row

#### 5. Insulator Material Option



- A = BK-PBT
- B = BK-PA66
- C = BK-PA6T
- D =BK-PA46
- E =BK-LCP

#### 6. Contact Plating

- A = Gold Flash
- B = 5U" Gold
- C = 10U" Gold
- D = 15U" Gold
- E = 30U" Gold
- F= Gold Flash/Tin
- G= Tin


#### 7. Post

- W (With Post)
- Ø (No Post)



#### (1). Packaging

Ø=PE Bag 1=Tray 2=Tube 3=Tube+Cap 4=Reel+Cap 5=Reel+Mylar

				OPERATION		DRAW	BEN	12.04.18	SCALE	FIT	 votre partenaire en électronique		
				X.X	±0.30				UNIT	mm			
				X.XX	±0.20	CHECK		SIZE	A4	PART NO.			2345S - 1 UXX - XXX
				X.XXX	±0.10	APPROVE		SHEET	1/1	TITLE:			2.00PF H4.5mm 1xNpin SMT Side Entry
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM	TOL			PROJ.					