






9	CLAMP NUT	NYLON	BLACK	1	
8	SEAL	SANTOPRENE, ID: 5.8mm.	BLACK	1	
7	HOOD	NYLON	BLACK	1	
6	S SEAL	SANTOPRENE.	BLACK	1	
5	O-RING	VITON.	BLACK	1	
4	SCREW NUT	NYLON+GF	BLACK	1	
3	CONTACT	BRASS, 6 u" GOLD PLATED. SOLDER BUCKET PIN.		n	
2	CONNECTOR	NYLON.		1	
1	O-RING	VITON	BROWN	1	
No.	PART NAME	DESCRIPTION	COLOR	QTY	REMARKS

REV.	DESCRIPTION	DATE
A	ISSUE	Sep/04/2008

- NOTES:
- ELECTRICAL CHARACTERISTICS:
CURRENT RATING: 2A / 5A
CONNECTOR TEMPERATURE RANGE: -40°C TO +105°C
DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
 - HOW TO ORDER: CAX-P2xxSA

- 02 - 2 PINS 05 - 5 PINS
- 03 - 3 PINS 06 - 6 PINS
- 04 - 4 PINS
- D - CURRENT RATING 5A
- N - CURRENT RATING 2A



PIN ASSIGNMENT FRONT VIEW



TITLE : CIRCULAR A SIZE FEMALE SCREW TYPE FIELD-ATTACHABLE PLUG

SCALE 1:1
UNLESS OTHERWISE SPECIFIED TOLERANCES:
X ±0.25 XX ± 0.1
XXX ± 0.05 ANGLE ± 1&X

REV. A SHEET 1/1
P/N: CAX-P2xxSA
DR: Stanley
CH: Micaela
DWC:NO: CAX-P2xxSA
AP: